

Tire Changer	TC400	TC530	TC950	TC660	TC950A
shipping weight	550	550	600	850	850
shipping dimensions	45"L x 38"W x 40"H	45"L x 38"W x 40"H	37"L x 48"W x 42"H	37"L x 48"W x 42"H 37"L x 48"W x 21"H (2 pieces)	37"L x 48"W x 42"H 37"L x 48"W x 21"H (2 pieces)
Max Rim Diameter (outside)	5"-21"	10"-20"	13"-24"	10"-20"	13"-24"
Max Rim Diameter (inside)	NA	12"-23"	15"-28"	12"-23"	15"-28"
Max Wheel Width	13"	3"-16" (3"-12")	3"-15"	3"-16"	3"-15"
Max Wheel Diameter	39"	38"	47"	41"	47"
Power Supply	110V	110V	110V	110V	110V 1.5HP (2HP)
Bead Breaker	2500KG/5511 Lbs	2500KG/5511Lbs	2500KG/5511 Lbs	2500KG/5511Lbs	2500KG/5511Lbs

Tire Changer	TC960	TC980	TC1000
shipping weight	860	1120	
shipping dimensions	37"L x 48"W x 42"H 37"L x 48"W x 21"H (2 pieces)	57"L x 45"W x 71"H 57"L x 45"W x 35"H (2 pieces)	
Max Rim Diameter (outside)	13"-24"	13"-24"	12"-30"
Max Rim Diameter (inside)	15"-28"	15"-28"	
Max Wheel Width	3"-15"	3"-15"	3"-15"
Max Wheel Diameter	47.5"	47"	47"
Power Supply	110V 147PSI	110V 2HP	110V
Bead Breaker	2500KG/5511Lbs	2500KG	2500KG